

PTFE GREASE



FLUORTEK LUBRICANTS

TP50 contains micronised fluoropolymer from Du Pont dispersed in isopropylalcohol. It is an effective lubricant with long life properties. Water repellent, doesn't soil, resists high (+260 Deg.C) and low (-70 Deg.C) temperatures. Non ageing and has extremely low friction.

Supplied in 1 litre bottles.

TP55 contains micronised fluoropolymer from Du Pont dispersed in silicone oil. It is an effective lubricant with long life properties. Water repellent, doesn't soil, resists high (+260 Deg.C) and low (-70 Deg.C) temperatures. Non ageing and has extremely low friction.

Supplied in cans 0.5, 1, 5, 10 and 25 kg or in 50 gram tubes with or without blister-pack.

TP56 contains micronised fluoropolymer from Du Pont dispersed in synthetic based oil with antioxidation additives. It is a unique lubricant with long life properties. Water repellent, doesn't soil, resists high (+260 Deg.C) and low (-70 Deg.C) temperatures. Non ageing and has extremely low friction.

Supplied in cans 0.5, 1, 5, 10 and 25 kg.

TP57 special lubricant for food, cosmetic and medical industry. Contains FDA approved micronised fluoropolymer from Du Pont dispersed in synthetic FDA approved oil. It is an effective lubricant with unique properties. Water repellent, doesn't soil, resists high (+260 Deg.C) and low (-70 Deg.C) temperatures. Non ageing and has extremely low friction.

Supplied in cans 0.5, 1,5, 10 and 25 kg.

PROPERTIES OF FLUORTEK LUBRICANTS

- Water repellent
- Resists saltwater
- Wide temperature range
- Non ageing, extremely long lifetime
- Extremely low friction
- High load-capacity under pressure